

# Videoregistratore digitale a 4 ingressi

## NLDVR774X



### NON PC-BASED

- Funzione di Motion detector
- Hard-Disk removibile fino a 200 Gbyte
- Funzioni Quad o schemo pieno
- Interfaccia allarmi completa
- Porta seriale RS232
- Facile utilizzo intuitivo
- Compressione video Wavelet
- Alta risoluzione video
- Ricerca per allarme o evento

Wavelet Compression Format replaces Time-Lapse VCR + Multiplexer

4 Audio inputs / 2 Audio outputs

4 level video quality adjustable: Best / High / Normal / Basic.

On Screen Display and RTC (Real time clock) Function

Multiplexing

- \* Support 4 Channels
- \* 4 Channels can record or display real-time recording images.
- \* 4 Channel loop back terminal

Resolution

Screen Modes	Resolution
Full screen	704(H) x 468(V) <NTSC> / 704(H) x 564(V) <PAL>
4 channels	352(H) x 234(V) <NTSC> / 352(H) x 282(V) <PAL>

Independent main and call monitor outputs allow simultaneous multi-camera or full screen viewing.

Multi Screen Display Mode

Below display modes are selectable while surveillance & DMR play back:



Full Screen Quad

Picture-In-Picture (PIP) is available in live and DMR playback mode, Zoom capability is up to 2 X 2 in live and DMR playback modes

Channels are swappable and each channel has independent title generator (up to 6 characters).

Motion trigger recording function and uses 15x12 target (NTSC) or 15x14 target (PAL) motion detection grids for each video channel.

Video Quality Adjustable on Each Channel: Color / Contrast / Brightness.

Parting line in the multi-channel display.

4 Channels alarm input, one alarm output and ALARM display.

Video loss detected on each channel can record 160 events.

Power-loss memory function: Original parameter will be remained in case of power failure.

Call Monitor: Switch Display

Support 1 Removable HDD (over 200GB), IDE Type

Timer: Schedule record

Display refresh rate up to 120 IPS (100 IPS for PAL)

Record refresh rate up to 25 IPS (18 IPS for PAL)

Quick Multiple Search by date/time, alarm, full list.

Fast and slow playback in multiple speeds.

Security password protection

RS-232, RS-485 communication protocol



Marco Ceruti

N.T.&T. nuova telefonia s.r.l.

V.le Lombardia 52/54

20093 Cologno Monzese MI